Plot 9, Pye Bridge Industrial Estate
Alfreton
Derbyshire
DE55 4NX
Tel: 01773 541372

SPECIFICATIONS: 12 CUYD OPEN SKIP

CONTAINER SPECIFICATIONS

BASE	4mm mild steel plate
SIDES & ENDS	4mm mild steel plate
REINFORMENT	RSC76mm x 38mm x 6.7kg/metre – DOUBLE RAIL on SIDES
GUSSETS	3mm Diamond gussets in each corner.
LIFTING LUGS	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
TIPPING BARS	30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END

PAINTING SPECIFICATIONS

OUTSIDE	High Build, zinc phosphate finish.

USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

(1) **ALL** plate seams fully welded – both inside and outside.
(5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
(6) **FACILITY** to weld on customer's asset numbers.
(7) **ALL STEEL** used is prime mild steel.
(8) **ALL SKIPS** have backing plates welded behind skip lugs.
(9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
(10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

OVERALL INTERNAL DIMENSIONS		
LENGTH	WIDTH	HEIGHT
13' 1"(3990mm)	5' 6" (1676mm)	5' 4" (1670mm)