

SPECIFICATIONS: 15 CUYD HEAVY DUTY OPEN HOOKLIFT CONTAINER

CONTAINER BODY SPECIFICATIONS

<u>BASE</u>	5mm mild steel plate (2 pieces)
<u>"A" FRAME</u>	RSC 150mm x 76mm x 18kg/metre with 10mm reinforcing plates with Rnd65mm dia. hook bar with deflector plate
<u>SIDES</u>	4mm mild steel plate - Optional 2 swages (folds)
<u>HEADBOARD</u>	4mm mild steel plate reinforced with RHS100mm x 100mm x 5mm
<u>VERTICAL CHANNELS</u>	PSC 135mm x75mm x 4mm (7 each side) – FULLY WELDED
<u>TOP RAIL</u>	RSC 150mm x 75mm x 18kg/metre

UNDERFRAME

<u>MAIN FRAME</u>	Twin runners of RSC 178mm x 76mm 20.84kg/metre with 60mm x 10mm wear strips and 5mm flitch plates
<u>FLOOR BEARERS</u>	7 no. PSC135mm x 75mm formed from 4mm mild steel
<u>ROLLERS</u>	Twin rollers 219mm diameter x 203mm long

DOOR ASSEMBLY SPECIFICATIONS

<u>ALL DOORS</u>	4mm mild steel plate. ALL hinges are fitted with grease points
<u>BARN DOORS</u>	Twin side opening double doors reinforced with RHS 80mm x 80mm x 3.6mm With primary and secondary locking mechanisms
<u>SINGLE DOOR</u>	Reinforced with RHS 80mm x 80mm x 3.6mm
<u>DOOR PILLARS</u>	RSC 150mm x 75mm x 18kg/metre

PAINTING SPECIFICATIONS

<u>INSIDE</u>	Optional One Coat primer only
<u>OUTSIDE</u>	One coat primer, One coat finishing in colour of your choice.



15 YD Heavy Duty No Goalpost

USEFUL OPTIONS INCLUDED IN ALL GMS'S HOOKLIFT PRICES

STRENGTH AND SAFETY

- (1) **ALL PLATE** seams fully welded – both inside and outside.
- (2) **9 UPRIGHTS** fully welded to side plates.
- (3) **4mm THICK** pressed channel floor bearers for extra floor
- (4) **PRIMARY AND SECONDARY** door locking facilities
- (5) **ALL HEADBOARDS** reinforced with RHS 100mm x 100mm x 5mm
- (7) **DEFLECTOR PLATE** fitted to headboard
- (8) **ALL STEEL** used is prime mild steel.

EASE OF USAGE AND SECURITY

- (1) **CUSTOMER'S ASSET NUMBERS** or letters welded (or burnt) – at NO extra charge
- (2) **ASSET** numbers welded on all containers for trace ability and security.
- (4) **LADDER** welded on one side's at headboard end
ROPE HOOKS welded all around container

OVERALL DIMENSIONS

Internal LENGTH 19'(5800mm)	Internal WIDTH 7'4" (2250mm)	Internal HEIGHT 3' (900mm)
External LENGTH 20' (6150mm)	External WIDTH 7'11" (2420mm)	External HEIGHT 3'10" (1180mm)