



Plot 9, Pye Bridge Industrial Estate  
Alfreton  
Derbyshire  
DE55 4NX  
Tel: 01773 541372

## SPECIFICATIONS: 6 CUYD DROP DOOR SKIP

### CONTAINER SPECIFICATIONS

|                         |                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------|
| <u>BASE</u>             | 4mm mild steel plate                                                                              |
| <u>SIDES &amp; ENDS</u> | 3mm mild sides & 4mm steel plate ends                                                             |
| <u>REINFORCEMENT</u>    | RSC76mm x 38mm x 6.7kg/metre – DOUBLE RAIL on SIDES                                               |
| <u>LIFTING LUGS</u>     | 4 no Sheppard Meiler type manufactured skip lugs welded through both the channels and side plates |
| <u>TIPPING BARS</u>     | 30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END                         |

### DOOR SPECIFICATIONS

|                     |                                                                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <u>GUSSETING</u>    | Substantial 3mm mild steel gusseting each side                                                                                                    |
| <u>DOOR DETAILS</u> | Lift up and open 3mm mild steel door reinforced with RSC 76 x 38mm<br>Door pivots on RSC76mm x 38mm and is fitted with secondary locking facility |

### PAINTING SPECIFICATIONS

|                |                                    |
|----------------|------------------------------------|
| <u>OUTSIDE</u> | High Build, zinc phosphate finish. |
|----------------|------------------------------------|



### USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

- (1) **ALL** plate seams fully welded – both inside and outside.
- (2) **FULLY GUSSETED** (with 3mm mild steel plate) all around door surround (to help prevent skip spreading when door is open)
- (3) **DOOR REINFORCED** with RSC76mm x 38mm x 6.7kg/metre for extra strength.
- (4) **LIFT UP AND OPEN** door to prevent accidental opening.
- (5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
- (6) **FACILITY** to weld on customer's asset numbers.
- (7) **ALL STEEL** used is prime mild steel.
- (8) **ALL SKIPS** have backing plates welded behind skip lugs.
- (9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
- (10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

| OVERALL INTERNAL DIMENSIONS |                         |                            |
|-----------------------------|-------------------------|----------------------------|
| LENGTH<br>10' 2" (3054mm)   | WIDTH<br>5' 6" (1676mm) | HEIGHT<br>4' 1/4" (1220mm) |