



Plot 9, Pye Bridge Industrial Estate
Alfreton
Derbyshire
DE55 4NX
Tel: 01773 541372

SPECIFICATIONS: 12 CUYD HEAVY DUTY OPEN SKIP

CONTAINER SPECIFICATIONS

<u>BASE</u>	5mm mild steel plate
<u>SIDES & ENDS</u>	4mm mild steel plate
<u>REINFORCEMENT</u>	RSC100mm x 50mm x 10.2kg/metre – DOUBLE RAIL on SIDES
<u>GUSSETS</u>	3mm Diamond gussets in each corner.
<u>LIFTING LUGS</u>	4 no Sheppard Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BARS</u>	30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END

PAINTING SPECIFICATIONS

<u>OUTSIDE</u>	High Build, zinc phosphate finish.
----------------	------------------------------------



USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

- (1) **ALL** plate seams fully welded – both inside and outside.
- (5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
- (6) **FACILITY** to weld on customer's asset numbers.
- (7) **ALL STEEL** used is prime mild steel.
- (8) **ALL SKIPS** have backing plates welded behind skip lugs.
- (9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
- (10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

OVERALL INTERNAL DIMENSIONS		
LENGTH	WIDTH	HEIGHT
13' 1" (3990mm)	5' 6" (1676mm)	5' 4" (1670mm)