



Plot 9, Pye Bridge Industrial Estate
Alfreton
Derbyshire
DE55 4NX
Tel: 01773 541372

SPECIFICATIONS: 8 CUYD DROP DOOR SKIP

CONTAINER SPECIFICATIONS

<u>BASE</u>	4mm mild steel plate
<u>SIDES & ENDS</u>	4mm mild steel plate
<u>REINFORCEMENT</u>	RSC76mm x 38mm x 6.7kg/metre – DOUBLE RAIL on SIDES
<u>LIFTING LUGS</u>	4 no Sheppard Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BARS</u>	30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END

DOOR SPECIFICATIONS

<u>GUSSETING</u>	Substantial 3mm mild steel gusseting each side
<u>DOOR DETAILS</u>	Lift up and open 3mm mild steel door reinforced with RSC 76 x 38mm Door pivots on RSC76mm x 38mm and is fitted with secondary locking facility

PAINTING SPECIFICATIONS

<u>OUTSIDE</u>	High Build, zinc phosphate finish.
----------------	------------------------------------



USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

- (1) **ALL** plate seams fully welded – both inside and outside.
- (2) **FULLY GUSSETED** (with 3mm mild steel plate) all around door surround (to help prevent skip spreading when door is open)
- (3) **DOOR REINFORCED** with RSC76mm x 38mm x 6.7kg/metre for extra strength.
- (4) **LIFT UP AND OPEN** door to prevent accidental opening.
- (5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
- (6) **FACILITY** to weld on customer's asset numbers.
- (7) **ALL STEEL** used is prime mild steel.
- (8) **ALL SKIPS** have backing plates welded behind skip lugs.
- (9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
- (10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

OVERALL INTERNAL DIMENSIONS		
LENGTH 11' 2" (3404mm)	WIDTH 5' 6" (1676mm)	HEIGHT 4' 1/4" (1220mm)