



Plot 9, Pye Bridge Industrial Estate
Alfreton
Derbyshire
DE55 4NX
Tel: 01773 541372

SPECIFICATIONS: 8 CUYD ENCLOSED SKIP

CONTAINER SPECIFICATIONS

<u>BASE</u>	4mm mild steel plate
<u>SIDES & ENDS</u>	4mm mild steel plate ends, 3mm mild steel sides & roof.
<u>LIDS</u>	3mm Dimond pressed lids OR DURAFLEX® plastic lids
<u>REINFORMENT</u>	RSC76mm x 38mm x 6.7kg/metre – SINGLE RAIL on SIDES
<u>LIFTING LUGS</u>	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BARS</u>	30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END

PAINTING SPECIFICATIONS

OUTSIDE High Build, zinc phosphate finish.



8 Cu.Yd. Enclosed Skip, Steel Lids

USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

- (1) **ALL** plate seams fully welded – both inside and outside.
- (5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
- (6) **FACILITY** to weld on customer's asset numbers.
- (7) **ALL STEEL** used is prime mild steel.
- (8) **ALL SKIPS** have backing plates welded behind skip lugs.
- (9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
- (10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

OVERALL INTERNAL DIMENSIONS		
LENGTH	WIDTH	HEIGHT
10' 1" (3050mm)	5' 6" (1676mm)	5' 6" (1680mm)