



Plot 9, Pye Bridge Industrial Estate
Alfreton
Derbyshire
DE55 4NX
Tel: 01773 541372

SPECIFICATIONS: 12 CUYD ENCLOSED SKIP

CONTAINER SPECIFICATIONS

<u>BASE</u>	4mm mild steel plate
<u>SIDES & ENDS</u>	4mm mild steel plate ends, 3mm mild steel sides & roof.
<u>LIDS</u>	3mm Dimond pressed lids OR DURAFLEX® plastic lids
<u>REINFORMENT</u>	RSC76mm x 38mm x 6.7kg/metre – SINGLE RAIL on SIDES
<u>LIFTING LUGS</u>	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
<u>TIPPING BARS</u>	30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END

PAINTING SPECIFICATIONS

OUTSIDE High Build, zinc phosphate finish.



12 Cu.Yd. Enclosed Skip, Steel Lids



12 Cu.Yd. Enclosed Skip, Plastic Lids

USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

- (1) **ALL** plate seams fully welded – both inside and outside.
- (5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
- (6) **FACILITY** to weld on customer's asset numbers.
- (7) **ALL STEEL** used is prime mild steel.
- (8) **ALL SKIPS** have backing plates welded behind skip lugs.
- (9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
- (10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

OVERALL INTERNAL DIMENSIONS		
LENGTH 11' 8" (3550mm)	WIDTH 5' 6" (1676mm)	HEIGHT 5' 11" (1810mm)