

SPECIFICATIONS: 15 CUYD STANDARD OPEN HOOKLIFT CONTAINER

CONTAINER BODY SPECIFICATIONS

<u>BASE</u>	5mm mild steel plate (2 pieces)
<u>"A" FRAME</u>	RSC 150mm x 76mm x 18kg/metre with 20mm reinforcing plates with Rnd65mm dia. hook bar with deflector plate
<u>SIDES</u>	3mm mild steel plate - Optional 2 swages (folds)
<u>HEADBOARD</u>	4mm mild steel plate reinforced with RHS100mm x 100mm x 5mm
<u>VERTICAL CHANNELS</u>	PSC 135mm x75mm x 4mm (7 each side) – FULLY WELDED
<u>TOP RAIL</u>	with RHS 80mm x 80mm x 3.6mm

UNDERFRAME

<u>MAIN FRAME</u>	Twin runners of RSC 178mm x 76mm 20.84kg/metre with 60mm x 10mm wear strips and 5mm flitch plates
<u>FLOOR BEARERS</u>	7 no. PSC135mm x 75mm formed from 4mm mild steel
<u>ROLLERS</u>	Twin rollers 219mm diameter x 203mm long

DOOR ASSEMBLY SPECIFICATIONS

<u>ALL DOORS</u>	3mm mild steel plate. ALL hinges are fitted with grease points
<u>BARN DOORS</u>	Twin side opening double doors reinforced with RHS 80mm x 80mm x 3.6mm With primary and secondary locking mechanisms
<u>SINGLE DOOR</u>	Reinforced with RHS 80mm x 80mm x 3.6mm
<u>DOOR PILLARS</u>	RSC 150mm x 75mm x 18kg/metre

PAINTING SPECIFICATIONS

<u>INSIDE</u>	Optional One Coat primer only
<u>OUTSIDE</u>	One coat primer, One coat finishing in colour of your choice.



15 yd Standard Front

USEFUL OPTIONS INCLUDED IN ALL GMS'S HOOKLIFT PRICES

STRENGTH AND SAFETY

- (1) **ALL PLATE** seams fully welded – both inside and outside.
- (2) **9 UPRIGHTS** fully welded to side plates.
- (3) **4mm THICK** pressed channel floor bearers for extra floor
- (4) **PRIMARY AND SECONDARY** door locking facilities
- (5) **ALL HEADBOARDS** reinforced with RHS 100mm x 100mm x 5mm
- (7) **DEFLECTOR PLATE** fitted to headboard
- (8) **ALL STEEL** used is prime mild steel.

EASE OF USAGE AND SECURITY

- (1) **CUSTOMER'S ASSET NUMBERS** or letters welded (or burnt) – at NO extra charge
- (2) **ASSET** numbers welded on all containers for trace ability and security.
- (4) **LADDER** welded on one side's at headboard end
- ROPE HOOKS** welded all around container

OVERALL DIMENSIONS

Internal LENGTH 19' (5800mm) External LENGTH 20' (6150mm)	Internal WIDTH 7'4" (2250mm) External WIDTH 7'11" (2420mm)	Internal HEIGHT 3' (900mm) External HEIGHT 3'10" (1180mm)
--	---	--