Plot 9, Pye Bridge Industrial Estate
Alfreton
Derbyshire
DE55 4NX
Tel: 01773 541372

SPECIFICATIONS: 7.5 CUYD DROP DOOR SKIP

CONTAINER SPECIFICATIONS

BASE	4mm mild steel plate
SIDES & ENDS	3mm mild sides & 4mm steel plate ends
REINFORMENT	RSC76mm x 38mm x 6.7kg/metre – DOUBLE RAIL on SIDES
LIFTING LUGS	4 no Shepperd Meiler type manufactured skip lugs welded through both the channels and side plates
TIPPING BARS	30mm mild steel tipping bar with FLT6mm pressed plate supports – EACH END

DOOR SPECIFICATIONS

GUSSETING	Substantial 3mm mild steel gusseting each side
DOOR DETAILS	Lift up and open 3mm mild steel door reinforced with RSC 76 x 38mm Door pivots on RSC76mm x 38mm and is fitted with secondary locking facility

PAINTING SPECIFICATIONS

OUTSIDE High Build, zinc phosphate finish.

USEFUL OPTIONS INCLUDED IN ALL GMS STANDARD OPEN SKIP PRICES

(1) **ALL** plate seams fully welded – both inside and outside.
(2) **FULLY GUSSETTED** (with 3mm mild steel plate) all around door surround (to help prevent skip spreading when door is open)
(3) **DOOR REINFORCED** with RSC76mm x 38mm x 6.7kg/metre for extra strength.
(4) **LIFT UP AND OPEN** door to prevent accidental opening.
(5) **SKIP LUGS** fitted through channels and side plate fitted with internal backing plate.
(6) **FACILITY** to weld on customer's asset numbers.
(7) **ALL STEEL** used is prime mild steel.
(8) **ALL SKIPS** have backing plates welded behind skip lugs.
(9) **ALL SKIPS** have both ends of tipping bar(s) capped in.
(10) **ALL SKIPS** have reflective chevrons & protector bars as standard.

OVERALL INTERNAL DIMENSIONS		
LENGTH	WIDTH	HEIGHT
10' 2"(3054mm)	5' 6" (1676mm)	4' ¼" (1220mm)